

ALLFASTENERS GAP FILLER

Description

Allfasteners Gap Filler is a premium quality general purpose acrylic based gap filler.

Pack Sizes

- 450g cartridge, product code 6003954042

Benefits

- Remains flexible – years after application.
- Easy to apply acrylic latex
- Tools and finishes perfectly
- Paintable
- Interior or exterior use
- Resists slump and sag
- No mess – water clean up
- Non-toxic and non-flammable

Uses

- Patching gaps around skirting boards, architraves, cornices, ceramic tiles (not in shower),
- Window frames prior to painting inside or outside.
- General purpose fit out finishing

Compatible Substrates

Drywall	Cement sheet
Cement render	Plasterboard
Brick	Aluminium
Timber	Ceramic

Coverage

450g cartridge will give approximately 15 lineal metres of a 5mm bead.

Limitations

- Do not apply to areas that will remain damp
- Not suitable in areas subject to water immersion or ponding water.
- Do not apply at temperatures below 5°C.
- Not suitable for tongue and groove boards.
- Not recommended where movement is greater than 10%.
- Not suitable as a hard surface filler
- Not suitable for areas subject to foot or vehicle traffic

- Do not apply over wet glue line to minimize discolouration due to bleed through of glue

Performance Summary

Colour	white
Skimming time	15 minutes
Extension at break	100%
Service temperature	-5°C to 80°C
Application temperature	+5°C to 35°C
Specific gravity	~1.5
Colour	Concrete grey

Surface Preparation

Ensure substrate surfaces are clean, sound, dry and free of oil, grease and surface contaminants such as dust, loose particles, release agents, silicone and water repellents. Ideally surfaces should be dry sealant will adhere to slightly damp surfaces, but avoid wet surfaces. Areas adjacent to joints may be masked to provide a neat finish. Masking should be removed immediately after tooling.

Priming

Priming is not normally required for application of Allfasteners Gap Filler™.

Application

Apply Allfasteners Gap Filler™ in ambient conditions between 5°C and 35°C. Higher temperatures should be avoided to prevent the possibility bubbling of the sealant due to rapid moisture evaporation. Do not apply below 5°C. Fill joint with caulking gun, then tool off with a spatula and clean off excess with a damp cloth. Protect from water for at least 48 hours until a suitable skin has cured (will require significantly longer at temperatures below 15°C).

Some shrinkage is normal during curing, and should be anticipated when applying gap filler.

Curing

The cure time of Allfasteners Gap Filler™ is temperature and humidity dependent, and also varies with thickness of application. In the summer months full cure may be achieved in two days. In winter it may take more than seven days for Allfasteners Gap Filler™ to dry. Allfasteners Gap Filler™ is rain resistant after 48 hours.

This technical data sheet summarises at the date of issue to the best of the knowledge of HB Allfasteners, the technical information of the product and in particular, how to safely handle and use the product in the workplace. Since HB Allfasteners Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this technical data sheet in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

ALLFASTENERS GAP FILLER

Painting

Allfasteners Gap Filler™ can be painted with most quality surface coating after three hours. For best results, paint after twenty four hours. When painting a sufficient thickness paint film must be used to allow any movement. Some ceiling paints and undercoats will crack when used over flexible fillers such as Allfasteners Gap Filler™. For best results, application of a flexible acrylic or oil based undercoat is recommended.

Clean Up

After applying Allfasteners Gap Filler™, clean all tools and surfaces with warm water while the sealant is still wet. Cured sealant will need to be removed mechanically.

Safety Information

Allfasteners Gap Filler™ is not classified as hazardous according to criteria of Worksafe Australia.

A Material Safety Data Sheet is available from your Allfasteners representative.

For Poisons Information Centre phone 13 11 26

This technical data sheet summarises at the date of issue to the best of the knowledge of HB Allfasteners, the technical information of the product and in particular, how to safely handle and use the product in the workplace. Since HB Allfasteners Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this technical data sheet in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

Customer Service Australia 1800 423 855 New Zealand 0800 225 873