

Product Technical Data Sheet

Allfasteners Megagrip Adhesive

Description:

Allfasteners Megagrip Adhesive is a high strength, polychloroprene rubber based adhesive / sealant supplied in a ready to use cartridge. It cures to form a tough, flexible heat resistant bond.

Allfasteners Megagrip I Adhesive is recommended for the bonding & sealing between a variety of substrates including wood, tile board, hard board, gyprock, steel, aluminium and cement sheet etc. It is ideal for the installation of most wallboards and interior panelling products.

Typical Properties:

Appearance:	Yellow paste
Viscosity:	Thick paste
Solids:	Approx. 25%
Specific Gravity:	Approx. 0.9

Directions for Use:

Surfaces to be bonded must be clean, dry and free from oil, grease, paint, dust etc.

1. Apply a 4 - 5 mm bead to each stud, batten or frame section to be covered. On flat surfaces, apply a bead around the perimeter and space zig zag beads 400mm apart vertically and horizontally.
2. Push the sheet into the position, ensuring that the adhesive is squeezed and spread onto the substrates.
3. Pull the sheet away from the wall approx. 300mm and allow to stand for 5 to 10 minutes.
4. Press the sheet firmly back into place. Use of a heavy roller or rubber mallet is recommended. For heavy sheets or materials some mechanical fixing may be needed as a temporary hold while the adhesive sets.
5. The joint will continue to gain strength for 2 to 3 days and maximum stress loading should not be applied until such time.

Coverage: A 300ml cartridge will form 15 meters of a 5mm bead.

Limitations:

Allfasteners Megagrip Adhesive is not suitable for polystyrene foam.

Storage and Handling:

Please read the Material Safety Data Sheet for this product BEFORE it is used.

Do not mix with other adhesives.

Keep covered when not in use to prevent contamination and drying out.

Product must be stored in compliance with local and federal storage regulations.

Store material between 15°C and 30°C away from sources of heat and direct sunlight.

Use only in a well ventilated area. Avoid breathing fumes or vapours and contact with skin.

Use strict stock rotation practices using the oldest batches first.

If the product is classed as a dangerous good, ensure that the product is stored in compliance with the applicable dangerous goods storage regulations. Refer to the products Material Safety Data Sheet for the dangerous goods classification.

Shelf Life:

Best used within 12 months from date of manufacture when stored under the above conditions in the original unopened containers.

Zecca Australia Pty Ltd

44 Little Napier Street

Fitzroy VIC 3065

Phone: (03) 9330 7777

Fax: (03) 9330 7755

User to satisfy itself as to the suitability of such information for its own particular purpose. In addition, any recommendation or suggestion made relating to the use of the information, either in this publication or in response to specific enquiry or otherwise, is given in good faith but it is for the prospective user to satisfy itself as to the suitability of any such information for its own particular purpose. No warranty is given as to the fitness of the information for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except insofar as such exclusion is prevented by law. No liability is accepted for loss or damage (including liability for negligence or other tortious act or omission other than that causing death or personal injury) arising from reliance on the information provided. Freedom from patent, copyright or design protection must not be assumed.

All Technical Data Sheets are uncontrolled documents, copies are not automatically updated.