

Zecca Australia Pty Ltd

Chemicals and Packaging Specialists

Material Safety Data Sheet

1. Statement of hazardous nature / Product and Company Identification

This product is classified as **HAZARDOUS** according to the criteria of NOHSC and a **Dangerous Good** by the criteria of the ADG Code

PRODUCT NAME: AUSpro 2349 Adhesive Cleaning Solvent

PRODUCT CODE: 3568 AUSpro 2349 Adhesive Cleaning Solvent, 20lt

SUPPLIER: Zecca Australia Pty Ltd
44 Little Napier Street
Fitzroy Vic 3065

Phone: (03) 9330 7777
Fax: (03) 9330 7755

2. Composition and Information on Ingredients

Chemical Entity	CAS No.	Proportion	R phrase
Hazardous constituents			
n-hexane	110-54-3	<5%	R11,R20,R48
Hexane Mixed Isomers		30-60%	R11, R38
Toluene	108-88-3	30-60%	R11, R20, R65
Non hazardous materials		to 100%	

No Other Hazardous materials are present in this product at concentrations above the cut off levels as Noted in the List of Designated Hazardous Substances, NOHSC:10005 (1999), or as defined in the Approved Criteria For Classifying Hazardous Substances,[NOHSC:1008(1999)].

A.I.C.S STATUS: All components of this finished product are listed on the A.I.C.S.

3. Hazards Identification

Emergency Overview: Highly flammable, harmful by inhalation, ingestion and by skin contact.

Acute

Swallowed: Moderately toxic. Tends to break up into a foam if the patient vomits. Upon aspiration into the lungs, chemical pneumonitis may develop.

Eye: Irritating to the eye.

Skin: Mildly irritating to the skin. Frequent or prolonged contact can cause skin complaints such as Dermatitis.

Inhaled: Irritating to the respiratory system. Prolonged exposure to vapours may cause headaches, impairment of judgement, Central Nervous System depression that in extreme cases can lead to unconsciousness or death.

Product: AUSPRO 2349

Date of issue: 11/04/06

Zecca Australia Pty Ltd

Chemicals and Packaging Specialists

Material Safety Data Sheet

Chronic: Inhalation: - Reports exist related to chronic toluene poisoning which indicate bone marrow and liver damage.

No Other Information Noted in This Section

4. First Aid Measures

Swallowed: DO NOT induce vomiting. Give 1-2 glasses of water and obtain medical assistance. Should the patient vomit, maintain a clear airway until medical assistance is obtained.

Eye: Flush with water for fifteen minutes. It is advisable to obtain Medical Advice concerning any eye injury.

Skin: Hose down with water before removing clothing due to possibility of static discharge igniting vapour. Wash affected areas with soap and water thoroughly. Allow clothing to thoroughly air dry then launder before re-use.

Inhaled: Carefully remove persons to fresh air, avoid becoming affected yourself. If patient is severely affected obtain medical assistance. If the person stops breathing apply artificial respiration and other first aid techniques as required until medical assistance is obtained.

Advice to Doctor :

Oral: - Gastrointestinal irritation, nausea, vomiting and cramping. CNS depression ranging from mild headache to anaesthesia and coma. Pulmonary irritation secondary to exhalation of solvent. Lavage with a cuffed tube if a large quantity is ingested. Aspiration is the main danger. Enforce bed rest & observe carefully & observe for 24 hours for chemical pneumonitis. Longer term medical surveillance may be necessary. Maintain airway & vital functions.

Inhalation: - CNS depression characterised by headache and dizziness that in extreme cases can lead to unconsciousness and death.

No Other Information Noted in This Section.

5. Fire Fighting Measures

Product is FLAMMABLE and does represent a FIRE and EXPLOSION HAZARD. Excessively heated sealed drums may rupture EXPLOSIVELY.

SOURCES OF IGNITION ADVICE: Isolate from of sources of heat, naked flames and sparks, including static discharges. Prevent build up of flammable vapours. Vapour and air mixtures may ignite explosively.

DANGEROUS DECOMPOSITION: Carbon dioxide, carbon monoxide and other unidentified thermal decomposition products

FIRE FIGHTING RECOMMENDATIONS: USE Water, Water fog, Foam, CO2 OR Dry Chemical

Product: AUSPRO 2349

Date of issue: 11/04/06

Zecca Australia Pty Ltd

Chemicals and Packaging Specialists

Material Safety Data Sheet

6. Accidental Release Measures

Wear rubber gloves and goggles in addition to respiratory protection for protection from splashes and vapours. Extinguish all ignition sources. Dam & recover. Prevent entry into drainage systems, rivers and waterways etc. Collect with absorbent material such as sand, earth or appropriate commercial absorbent. Shovel up with non-sparking tools then PLACE INTO SUITABLE CONTAINERS. Empty containers may contain product residue. Follow safety procedures until container has been cleaned.

7. Handling and storage

Store on a wooden pallet. Store between 0 – 30C. Should recommended max. storage temperature be exceeded, cool sealed container under running water for 30 minutes before use. Excessively heated sealed drums may rupture EXPLOSIVELY. Keep away from heat, naked flames or sparks including static discharges. Use appropriate earthing techniques when transferring liquid from one container to another. Store away from oxidising agents. Keep containers closed at all times when not in use.
DANGEROUS GOODS CLASS/SUBSIDIARY RISK: Class 3 Flammable Liquid, Packaging Group II

8. Exposure Controls & Personal Protection

Exposure: This material contains the following materials for which exposure limits have been set by NOHSC AUSTRALIA, as listed in the "National Exposure Standards [NOHSC:3008 (1995)]." and Amendments to Adopted National Exposures Standards for Atmospheric Contaminants in the Occupational Environment (Source A Updates Batch 1) 2002 : -

n-hexane	110-54-3	TWA: 20 ppm STEL: NOT NOTED
Other isomers of hexane		TWA: 500 ppm STEL: 1,000 ppm
Toluene	108-88-3	TWA: 50 ppm STEL: 150 ppm

Ventilation: - Provide explosion proof ventilation sufficient to maintain exposure levels below the listed exposure limits.

Personal Protection:

Respiratory type (AS1716) Organic Vapour Mask if exposed to mist or vapours at up to 10 times the exposure limit. Above this level use air supplied or self contained breathing apparatus.

Glove Type: Impervious gloves should be worn to prevent skin contact. Consult Industrial glove supplier for a suitable glove.

Eye: Goggles or Face shield to avoid splashes.

Clothing: Sufficient to avoid skin contact

Product: AUSPRO 2349

Date of issue: 11/04/06

Zecca Australia Pty Ltd

Chemicals and Packaging Specialists

Material Safety Data Sheet

9. Physical and Chemical Properties

Appearance:	Clear Liquid
Flash Point:	< -26C
Boiling Point:	Approx 55°C
Flammability Limits:	Upper UEL 7.5 % v/v Lower LEL 1.1 % v/v

Vapour Pressure @ 760 mm Hg @ 25 deg C:	not known
Solubility in water:	Immiscible
Specific Gravity:	Approx. 0.78
Evaporation Rate (Butyl Acetate= 1):	not determined
Other Data:	none noted

Major recommended usage:	Specialised applications including Solvent for polychloroprene adhesives
Method of Application:	Mechanical

10. Stability and Reactivity

Reactivity: Stable at normal temperatures and pressure.

11. Toxicological Information

n-hexane:	Inhalation-Human Oral rat	TCLo: 190 ppm/8W: Peripheral nervous system effects LD50: 28,710 mg/kg
Toluene:	Oral Rat Skin Rabbit	LD50: 5000 mg/kg LD50: 12124 mg/kg

No other data noted.

12. Ecological Information

Environmental Information: no data available for this product. Do not allow to enter the environment. Waste Material should be collected and disposed of according to the relevant Local/State or Federal Regulations.

Product: AUSPRO 2349

Date of issue: 11/04/06

Zecca Australia Pty Ltd

Chemicals and Packaging Specialists

Material Safety Data Sheet

13. Disposal

Refer to Land Waste Management Authority.

14. Transport Information

This material is a Class 3 Flammable Liquid according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

Proper Shipping Name:	Flammable liquid N.O.S. (i) immiscible with water
U.N. NO.:	1993
DANGEROUS GOODS CLASS:	3.1
SUBSIDIARY RISK:	None Allocated
HAZCHEM CODE:	3(Y)E
Packaging Group:	II
POISON SCHEDULE:	S6

15. Regulatory Information

Hazard Classification: Harmful Xn Xi

Risk Phrases:

R11	Highly flammable
R20	Harmful by inhalation
R36/37/38	Irritating to eyes, respiratory system and skin
R65	Harmful; may cause lung damage if swallowed
R67	Vapours may cause drowsiness and dizziness

Safety Phrases:

S9	Keep container in a well ventilated place
S16	Keep away from sources of ignition No Smoking
S24	Avoid contact with skin
S25	Avoid contact with eyes
S29	Do not empty into drains
S33	Take precautionary measures against static discharge
S51	Use only in well ventilated areas

Product: AUSPRO 2349

Date of issue: 11/04/06

Zecca Australia Pty Ltd

Chemicals and Packaging Specialists

Material Safety Data Sheet

16. Other Information

Contact Point:

Australia
Zecca Australia Pty Ltd
44 Little Napier Street
Fitzroy Vic 3065

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchasers' responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.

Product: AUSPRO 2349

Date of issue: 11/04/06