

MATERIAL SAFETY DATA SHEET FOR : MAXBOND FAST GRIP

Replaces: April 2005. Date of issue: Septemebr 2007

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Maxbond fast grip

Other Names: Not applicable

Recommended Use: Water borne acrylic adhesive used in the construction industry to bond a variety of substrates. Apply in a bead form directly out of the cartridge using a caulking gun.

Company: HB Fuller

Address: 16-22 Red Gum Drive, Dandenong South VIC 3175

Telephone: (03) 9797 6222

Emergency Telephone No: 1800 033 111

2. HAZARD IDENTIFICATION*Not classified as hazardous according to criteria of Worksafe Australia***3. COMPOSITION**

Ingredients:

CHEMICAL ENTITY	CAS NO	PROPORTION
Calcium carbonate	1317-65-3	High
Water	7732-18-5	Med
Acrylic copolymer	Not available	Med
Other ingredients determined not to be hazardous	Not applicable	Low

Low <10%

Med. 10-30%

High 30-60%

V High >60%

4. FIRST AID MEASURES

Swallowed:

If swallowed, do NOT induce vomiting. Give one glass of water or milk. Seek medical advice. Never give anything by mouth to an unconscious person.

Eyes:

Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

Skin:

Wash with soap and water. Get medical attention if irritation develops or persists.

Inhaled:

MATERIAL SAFETY DATA SHEET FOR : MAXBOND FAST GRIP

Replaces: April 2005. Date of issue: Septemebr 2007

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Contact a doctor is symptoms persist.

First Aid Facilities:

Have eye wash available when exposure may occur

Advice to Doctor

Treat symptomatically

5. FIRE FIGHTING MEASURES

Flash point:	Not established
Auto ignition temperature	Not established
Lower explosive limit (% in air):	Not established
Upper explosive limit (% in air):	Not established
Extinguishing media:	Use water spray, foam, dry chemical or carbon dioxide.
Unusual fire and explosion hazards:	None
Special fire fighting instructions:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
Hazardous combustion products:	In the dry state, burning will emit carbon monoxide and other hazardous fumes

6. ACCIDENTAL RELEASE MEASURES

Special protection:	Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred.
Clean-up:	Contain - prevent contamination of waterways and drains. If the quantity spilled warrants it, immobilise it first using an absorbent and then transfer to a suitably labelled and sealable containers for disposal. Dispose strictly in accordance with local industrial waste disposal and environmental protection regulation.

7. HANDLING AND STORAGE

Handling:	Not considered Dangerous Goods as defined by the Australian Code for the Transport of Dangerous Goods by Road and Rail
Storage:	Store in a cool dry place. Do not store in direct sunlight or below 5°C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards [NOHSC: 1004 (2004)].

Chemical	CAS number	TWA	TWA	STEL	STEL
----------	------------	-----	-----	------	------

MATERIAL SAFETY DATA SHEET FOR : MAXBOND FAST GRIP

Replaces: April 2005. Date of issue: Septemebr 2007

		ppm	Mg/m3	(ppm)	(mg/m3)
Butyl acrylate	141-32-2	10	55	-	-

Engineering Controls:
Local exhaust ventilation is preferred

Personal Protection:
Eye protection: Wear safety glasses when handling this product.
Skin protection: Avoid skin contact by wearing chemically resistant gloves. Skin absorption may potentially contribute to the overall exposure to this material.
Gloves: Chemically impervious
Respiratory protection: Not normally required
Ventilation: Use local exhaust ventilation or other engineering controls to minimize exposures.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Thick coloured paste
Colour:	Various
Odor:	Sweet
Odor threshold:	Not established
Weight per litre: (Kg)	1.4
Specific gravity:	1.4
Solids (% by weight):	Not established
pH:	Not established
VOC content	14g per litre
(Californian South coast air quality management rule 1168)	

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of temperature and humidity
Chemical incompatibility:	None established
Hazardous :	Will not occur.
Hazardous decomposition product:	Carbon monoxide and other harmful gases may be emitted upon burning.

11. TOXICOLOGICAL INFORMATION

Potential health effects by route of exposure

Eye:
Direct eye contact with the product may cause irritation.

Skin:

MATERIAL SAFETY DATA SHEET FOR : MAXBOND FAST GRIP

Replaces: April 2005. Date of issue: Septemebr 2007

Mild irritant.

Inhalation:

Vapour pressure is so low that inhalation does not present a problem under normal conditions. No adverse effects are expected.

Ingestion:

No data is available. No adverse effects are expected. May cause abdominal discomfort if swallowed in large quantities.

Long term (chronic) health effects

Reproductive: None established

Target organ(s): Lungs: The calcium carbonate in this product may contain a small amount of respirable crystalline silica. Respirable crystalline silica has been classified as a Group 2A carcinogen (The agent is probably carcinogenic to humans) by IRAC. Chronic exposure to high levels of crystalline silica may lead to impaired lung function and cause silicosis. This hazard is not present in the product as supplied. However when cutting, sanding or drilling the DRY product with power tools, a suitable dust mask (for selection guide see AS 1715) should be worn.
Skin: Repeated or prolonged contact with product may cause irritation of eyes or skin.

Existing health conditions affected by exposure:

None established

12. ECOLOGICAL INFORMATION

Overview: No ecological information available

13. DISPOSAL

Dispose strictly in accordance with local industrial waste disposal and environmental protection regulation.

14. TRANSPORT INFORMATION

Manufacturer's Code: Not applicable

UN Number: None assigned

Dangerous Goods Class: None assigned

Subsidiary Risk: None assigned

Hazchem Code: None assigned

Poisons Schedule: Not scheduled

Packaging Group: None assigned

Storage and Transport: This product is a not Dangerous Good for the purpose of transport.

DOT:

IATA:

MATERIAL SAFETY DATA SHEET FOR : MAXBOND FAST GRIP

Replaces: April 2005. Date of issue: Septemebr 2007

15. REGULATORY INFORMATION

All components of this material are registered with Nicnas and appear on the AICS.

16. OTHER INFORMATION

Contact point: Technical Manager (03) 9797 6222

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular, how to safely handle and use the product in the workplace. Since H.B. Fuller Company Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.
