



H.B. Fuller Company

Fuller
WORLD LEADER IN ADHESIVES

MATERIAL SAFETY DATA SHEET FOR: FLOOR BOND XMS

Replaces: July 2006 Date of issue: September 2007

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: FLOORBOND XMS
Other Names: Not applicable
Recommended Use: Adhesive for flooring, apply with a trowel.

Company: H. B. Fuller Company
Address: 16-22 Red Gum Drive, Dandenong South VIC 3175
Telephone: (03) 9797 6222
Emergency Telephone No: 1800 033 111

2. HAZARD IDENTIFICATION

Not classified as hazardous according to criteria of the NOHSC

3. COMPOSITION

No Hazardous Ingredients

4. FIRST AID MEASURES

Swallowed:
Rinse mouth with water. Never give water to an unconscious person. Do not induce vomiting. Seek medical advice.

Eyes:
Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

Skin:
Rinse with soap and water. Get medical attention if irritation develops or persists.

Inhaled:
Remove to fresh air. Seek medical advice.

First Aid Facilities:
Have eye wash available when exposure may occur

Advice to Doctor
Treat symptomatically. Substance is a polymer that reacts with moisture to cure. Moisture on skin will react with this product.

MATERIAL SAFETY DATA SHEET FOR: FLOOR BOND XMS

Replaces: July 2006 Date of issue: September 2007

5. FIRE FIGHTING MEASURES

FLASH POINT:	> 240 degrees C
AUTOIGNITION TEMPERATURE:	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
UPPER EXPLOSIVE LIMIT (% in air):	Not established
EXTINGUISHING MEDIA:	Use water spray, polyvalent foam, dry chemical, ABC powder or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	On burning, will release carbon monoxide, carbon dioxide and formation of small quantities of nitrous vapours and hydrogen chloride.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

6. ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:	Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred.
CLEAN-UP:	Ensure adequate ventilation. Contain - prevent contamination of waterways and drains. Immobilise using an absorbent and transfer to a suitable container for disposal. Dispose of in accordance with local authority guidelines.

7. HANDLING AND STORAGE

Handling: Observe normal hygiene standards.

Storage: Store in a cool, dry area. Keep container closed. Keep away from water / moisture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards [NOHSC: 1004 (2004)]. N/A

Engineering Controls: Local exhaust ventilation is preferred

Personal Protection:

EYE PROTECTION:	Wear safety glasses when handling this product.
SKIN PROTECTION:	Avoid skin contact by wearing rubber or PVC gloves.

RESPIRATORY PROTECTION: Respiratory protection not required in normal conditions.

VENTILATION: Use local exhaust ventilation or other engineering controls to minimize exposures.



H.B. Fuller Company



MATERIAL SAFETY DATA SHEET FOR: FLOOR BOND XMS

Replaces: July 2006 Date of issue: September 2007

Dangerous Goods Class: Not applicable
Subsidiary Risk: None assigned
Hazchem Code: None assigned
Poisons Schedule: Not scheduled
Packaging Group: Not applicable
Storage and Transport: This product is not a Dangerous Good for the purpose of transport.

DOT: Not subject
IATA: Not subject

15. REGULATORY INFORMATION

All components of this material are registered with NICNAS and appear on the AICS.

16. OTHER INFORMATION

Contact point: Technical Manager (03) 9797 6222

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular, how to safely handle and use the product in the workplace. Since H.B. Fuller Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.