



MATERIAL SAFETY DATA SHEET FOR: TRADE MATE INTERIOR POWDER FILLER

Replaces: July 2003. Date of issue: September 2007

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Trademate Interior Powder Filler
Other Names: Not applicable
Recommended Use: Decorators Filler

Company: H. B. Fuller Company
Address: 16-22 Red Gum Drive, Dandenong South VIC 3175
Telephone: (03) 9797 6222
Emergency Telephone No: 1800 033 111

2. HAZARD IDENTIFICATION

Not classified as hazardous according to criteria of Worksafe Australia

3. COMPOSITION

CHEMICAL ENTITY	CAS NO	PROPORTION
Plaster	10034-76-1	High
Calcium Carbonate	1317-65-3	High
Mica	12001-26-2	Low
Starch	9004-53-9	Low
Polyvinyl Alcohol	25213-24-5	Low
Cellulose Thickener	9004-67-5	Low
Lime	1305-62-0	Low

Low <10% Med. 10-30% High 30-60% V High >60%

4. FIRST AID MEASURES

Swallowed:

Do NOT induce vomiting. Give large amounts of water to drink. Seek medical attention. Never give anything by mouth to an unconscious person. Lean victim forward to reduce the risk of aspiration.

Eyes:

If in eye, irrigate immediately with copious amounts of water for 15 minutes with eyelids held open. See a doctor.

Skin:

Wash affected areas with copious quantities of soap and water immediately. Remove contaminated clothing and wash before reuse. See a doctor if irritation persists.

Inhaled:

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical attention if discomfort continues

MATERIAL SAFETY DATA SHEET FOR: TRADE MATE INTERIOR POWDER FILLER

Replaces: July 2003. Date of issue: September 2007

First Aid Facilities:

Have eyewashes available where contact with eye is likely and safety shower where bodily contact may occur

Advice to Doctor

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flash point:	Not established
Auto ignition temperature	Not established
Lower explosive limit (% in air):	Not established
Upper explosive limit (% in air):	Not established
Extinguishing media:	Use water spray, foam, dry chemical or carbon dioxide.
Unusual fire and explosion hazards:	None
Special fire fighting instructions:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
Hazardous combustion products:	Carbon monoxide and other hazardous fumes may be released when the product is burned.

6. ACCIDENTAL RELEASE MEASURES

Special protection:	Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred.
Clean-up:	Vacuum or sweep up spill. Dispose strictly in accordance with local industrial waste disposal and environmental protection regulation.

7. HANDLING AND STORAGE

Handling:	Not considered Dangerous Goods as defined by the Australian Code for the Transport of Dangerous Goods by Road and Rail
Storage:	Store in a cool dry place. Do not store in direct sunlight or below 5°C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards [NOHSC: 1003 (1995)].

Chemical	CAS number	TWA ppm	TWA Mg/m3	STEL (ppm)	STEL (mg/m3)
Dust NOS (not otherwise specified):	-	10	-	-	-

MATERIAL SAFETY DATA SHEET FOR: TRADE MATE INTERIOR POWDER FILLER

Replaces: July 2003. Date of issue: September 2007

Crystalline silica	14808-60-7	-	0.1	-	-
mica	-	-	2.5	-	-

Dust NOS (not otherwise specified): 10mg/m³ TWA (time weighted average) as inspirable dust.Crystalline Silica (quartz): 0.2mg/m³ TWA as respirable dust.Mica: 2.5mg/m³ TWA as inspirable dust**Engineering Controls:**

Avoid generating dust. Where dust may be generated while handling or mixing, local dust extraction is recommended. If dust is created when using power operated equipment for sanding or drilling the hardened product. An enclosed or poorly ventilated area local dust extraction is recommended. Work areas should also be cleaned regularly by wet sweeping or vacuuming.

Eye protection:	Wear safety glasses when handling this product.
Skin protection:	Avoid skin contact by wearing chemically resistant gloves. Skin absorption may potentially contribute to the overall exposure to this material.
Gloves:	Chemically impervious
Respiratory protection:	Not normally required
Ventilation:	Where dust may be generated while handling or mixing, local dust extraction is recommended. If dust is created when using power operated equipment for sanding or drilling the hardened product

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Free flowing powder
Colour:	Grey
Odor:	None
Odor threshold:	Not established
Weight per litre: (Kg)	2.67
Specific gravity:	2.67
Solids (% by weight): VOC content (Californian South coast air quality management rule 1168):	zero

10. STABILITY AND REACTIVITY**Chemical Stability:**

Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure

Hazardous Polymerisation:

None

Incompatibilities:

None

11. TOXICOLOGICAL INFORMATION

**MATERIAL SAFETY DATA SHEET FOR: TRADE MATE INTERIOR POWDER
FILLER**

Replaces: July 2003. Date of issue: September 2007

Health Effects**ACUTE:****Swallowed:**

Unlikely under normal conditions of use, but swallowing the dust from this product may result in abdominal discomfort.

Eye:

Dust from this product may irritate the eyes, causing watering and redness

Skin:

Dust from this product may cause irritation of the skin from friction but is not absorbed through the skin.

Inhaled:

Dust from this product may cause irritation of the nose, throat and lungs, causing coughing and sneezing. Unlikely to cause a health hazard in the form supplied

CHRONIC:**Reproductive:**

None established

Target organ(s):

Lungs: Respirable crystalline silica has been classified as a Group 2A carcinogen (The agent is probably carcinogenic to humans) by IRAC. Chronic exposure to high levels of crystalline silica may lead to impaired lung function and cause silicosis. When cutting, sanding or drilling the DRY product with power tools, a suitable dust mask (for selection guide see AS 1715) should be worn

12. ECOLOGICAL INFORMATION

No information available

13. DISPOSAL

Dispose strictly in accordance with local industrial waste disposal and environmental protection regulation.

14. TRANSPORT INFORMATION

Manufacturer's Code: Not applicable

UN Number: Not assigned

Dangerous Goods Class: None assigned

Subsidiary Risk: None assigned

Hazchem Code: None assigned

Poisons Schedule: Not scheduled

Packaging Group: None assigned

Storage and Transport:

This product is not a Dangerous Good for the purpose of transport. No special transport precautions are required.

15. REGULATORY INFORMATION

All components of this material are registered with Nicnas and appear on the AICS.



H.B. Fuller Company

Fuller
WORLD LEADER IN ADHESIVES

MATERIAL SAFETY DATA SHEET FOR: TRADE MATE INTERIOR POWDER
FILLER

Replaces: July 2003. Date of issue: September 2007

16. OTHER INFORMATION

Contact point: Technical Manager (03) 9797 6222

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular, how to safely handle and use the product in the workplace. Since H.B. Fuller Company Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.