

FOAMING TYRE & ENGINE DEGREASER

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	Foaming Tyre & Engine	53 ASSEMBLY DRIVE
Manufacturers Code:	FTE25	TULLAMARINE VIC 3043
Date:	1 November 2006	(03) 9338 6655 (BH) (03) 9336 7945 (AH)

STATEMENT OF HAZARDOUS NATURE: HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

IDENTIFICATION

U/N No	N/A	Dangerous Goods Class	N/A
Hazchem Code	N/A	Poisons Schedule	N/A

PHYSICAL DESCRIPTION / PROPERTIES

Appearance:	Green Liquid	Odour:	Butyl
Autoignition Temperature:	N/A	Flash Point(°C):	N/A
Boiling Point (°C):	(°C): 100	Flammability Limits(%):	N/A
Vapour Pressure:	N/A	Solubility in Water:	Complete
Specific Gravity (20°C):	1.2	Vapour Density:	N/A
Evaporation Rate:	N/A	Percent Volatiles:	N/A

INGREDIENTS:

Chemical Entity	W%W	CAS No:	UN No:
2-Butoxyethanol	<5%	111-76-2	2369
Sodium Hydroxide	<5%	1310-73-2	1823/1824
Sodium Metasilicate	<5%	10213-79-3	N/A
Phosphates	<5%	7758-29-4	N/A
Formalin	<1%	50-00-0	1198/2209

SAFE HANDLING INFORMATION

Storage & Transport:	Not dangerous goods for transport. Store in a cool dry area, away from strong acids or oxidizers.
Spills & Leaks:	Ventilate area. Pick up with absorbent material.
Waste Disposal:	Treat as hazardous waste. Do not allow to enter sewers or any body of water.
Fire & Explosion Data:	Not normally applicable. Remove from fire areas if possible. Use self-contained breathing apparatus for fire fighting.

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Swallowed:	Vomiting diarrhoea
Eye:	Irritation. Overexposure may be damaging.
Skin:	Irritation. Dermatitis may be aggravated by exposure. Overexposure may be damaging.
Inhaled:	Irritation to nose and throat, can cause headaches.

TREATMENT

Swallowed:	DO NOT induce vomiting. Give two to three glasses of water and call a physician immediately.
Eye:	Flush with large amounts of water for 15 minutes.
Skin:	Remove contaminated clothing and wash area well with soap and water.
Inhaled:	Remove to fresh air. Give artificial respiration if necessary.

FOAMING TYRE & ENGINE DEGREASER

MATERIAL SAFETY DATA SHEET

MSDS No:		
Product Name:	Foaming Tyre & Engine	QUICK SMART PRODUCTS
Manufacturers Code:	FTE25	53 ASSEMBLY DRIVE
Date:	1 November 2006	TULLAMARINE VIC 3043
		(03) 9338 6655 (BH)
		(03) 9336 7945 (AH)

PRECAUTIONS FOR USE:

Exposure Standards:	See ingredients.
Ventilation:	Ventilate to prevent accumulation of vapours. Use mechanical means if necessary.
Personal Protection:	Wear chemically protective gloves and safety glasses. Use splash apron and boots. If splashing occurs use NIOSH / MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.
Flammability:	NFPA: 0 HMIS: 0

CONTACT POINT

Contact:	WALTER DAY
-----------------	------------