

PETROLEUM JELLY

MATERIAL SAFETY DATA SHEET

MSDS No: Product Name: Manufacturers Code: Date:	Snow White Petroleum Jelly PJ400, PJ35, PJ20 23 March 2007	QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043 (03) 9338 6655 (BH) (03) 9336 7945 (AH)
---	--	--

STATEMENT OF HAZARDOUS NATURE: *NON HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA*

IDENTIFICATION

U/N No	N/A	Dangerous Goods Class	N/A
Hazchem Code	N/A	Poisons Schedule	N/S

PHYSICAL DESCRIPTION / PROPERTIES

Appearance:	Soft Off White Paste/solid	Odour:	None
Auto ignition Temperature:		Flash Point (°C):	>200°C
Boiling Point (°C):	N/A	Flammability Limits (%):	N/A
Vapour Pressure:		Solubility in Water:	Negligible
Specific Gravity (20°C):	0.85	Vapour Density:	
Evaporation Rate:		Percent Volatiles:	

INGREDIENTS:

Chemical Entity	W%W	CAS No:	UN No:
Petrolatum based product		N/R	

SAFE HANDLING INFORMATION

Storage & Transport: Spills & Leaks: Waste Disposal: Fire & Explosion Data:	Classified as a C2 combustible liquid for storage and handling purposes. Store in a cool, dry well ventilated area, out of direct sunlight. Avoid sparks, flames and other ignition sources. Remove all sources of ignition. Wear protective clothing. If possible contain the spill. Place inert, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. If large quantities of this material enter the waterways contact the EPA or your local Waste Management Authority. Dispose of waste according to federal, EPA, state and local regulations. Extinguishing media: Carbon dioxide, foam or dry chemical. Do not use water jets. Cool fire exposed containers with water spray. Combustible liquid. Fire-exposed container may rupture/explode.
--	---

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Swallowed: Eye: Skin: Inhaled:	May cause irritation of the gastrointestinal system. Symptoms may include nausea, vomiting and diarrhoea. May cause eye irritation, resulting in redness, stinging and lachrymation. Molten product may cause severe burns and possible permanent corneal damage to the eye i.e. blindness. May cause irritation in contact with the skin to sensitive individuals. Molten product may cause severe burns and possible permanent scarring. May cause irritation to the mucous membrane and upper airways, where materia is heated and vapours are generated and/or in poorly ventilated areas. Symptoms may include headache, dizziness and nausea.
---	--

PETROLEUM JELLY

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	Snow White Petroleum Jelly	53 ASSEMBLY DRIVE
Manufacturers Code:	PJ400, PJ35, PJ20	TULLAMARINE VIC 3043
Date:	23 March 2007	(03) 9338 6655 (BH) (03) 9336 7945 (AH)

TREATMENT

Swallowed:	Do not induce vomiting. Immediately wash out mouth with water. Seek medical attention.
Eye:	Wash with copious amounts of water, holding eyelids open. If irritation develops or persists, seek medical attention. In case of contact with molten product, flush immediately with water and seek immediate medical attention.
Skin:	Remove contaminated clothing. Wash gently and thoroughly with water and non-abrasive soap. If irritation develops seek medical attention. In case of contact with molten product, cool immediately with lukewarm water. Do not try to remove product that has stuck to skin. Seek immediate medical attention.
Inhaled:	Remove the source of contamination or move victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a facemask if breathing is difficult. If irritation develops or persists, seek medical attention.

PRECAUTIONS FOR USE:

Exposure Standards:	No value assigned for this specific material.
Ventilation:	Avoid breathing of vapours or mists. Where ventilation is inadequate and vapours or mists are generated the use of an approved respirator with organic vapour/particulate filter complying with AS/NZS 1715 and AS/NZS 1716 is recommended.
Personal Protection:	Safety glasses or face shield as appropriate. Impervious gloves recommended. Wear appropriate protective clothing including chemical resistant apron where clothing is likely to be contaminated
Flammability:	Combustible liquid. Fire exposed container may rupture/explode.

CONTACT POINT

Contact:	WALLY DAY
-----------------	-----------