

VINYL PLUS

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	Vinyl Plus	53 ASSEMBLY DRIVE
Manufacturers Code:	VP1, VP5, VP20	TULLAMARINE VIC 3043
Date:	1 August 2006	(03) 9338 6655 (BH)
		(03) 9336 7945 (AH)

STATEMENT OF HAZARDOUS NATURE: NON HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

IDENTIFICATION

U/N No	N/A	Dangerous Goods Class	N/A
Hazchem Code	N/A	Poisons Schedule	N/A

PHYSICAL DESCRIPTION / PROPERTIES

Appearance:	Opaque White Liquid	Odour:	Pleasant Odour
Autoignition Temperature:	N/A	Flash Point (°C):	N/R
Boiling Point (°C):	100°C (Approx)	Flammability Limits (%):	NON FLAMMABLE
Vapour Pressure:	18 mm Hg @ 20°C	Solubility in Water:	SOLUBLE
Specific Gravity	1.0 Approx	Vapour Density:	N/A
Evaporation Rate:	As for water	Percent Volatiles:	> 60% (Water)

INGREDIENTS:

Chemical Entity	W%W	CAS No:	
Water H2O	> 60%	7732-18-5	
Polydimethylsiloxane (C2-H6-O-Si)x	10-30%	9016-00-6	
Surfactants	< 10%	N/A	
Perfume	< 10%	N/A	

SAFE HANDLING INFORMATION

Storage & Transport:	Store in a cool, dry, well-ventilated area, away from oxidising agents, acids and foodstuffs.
Spills & Leaks:	If spilt, absorb with sand or similar.
Waste Disposal:	Ensure appropriate measures are taken to prevent this product from entering the environment. Dispose of in accordance with relevant local legislation.
Fire & Explosion Data:	Non-Flammable. If product is present in a fire, toxic gases may be evolved. Evacuate area and contact emergency services. Wear full protective clothing including SCBA when combating fire. Use waterfog to cool intact containers and nearby storage areas.

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Swallowed:	Low toxicity. Ingestion of large doses may result in nausea, vomiting and gastrointestinal irritation.
Eye:	Low irritant. May cause irritation, lacrimation and conjunctivitis.
Skin:	Low irritant. Prolonged and repeated contact may result in irritation, skin rash and dermatitis.
Inhaled:	Low irritant. Over exposure to mists or vapours (if sprayed) may result in mucous membrane irritation of the nose and throat with coughing. At high levels nausea, dizziness and headache.

VINYL PLUS

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	Vinyl Plus	53 ASSEMBLY DRIVE
Manufacturers Code:	VP1, VP5, VP20	TULLAMARINE VIC 3043
Date:	1 August 2006	(03) 9338 6655 (BH) (03) 9336 7945 (AH)

TREATMENT

Swallowed:	For advice, contact a Poisons Information Centre on 13 11 26 or a doctor. If swallowed do not induce vomiting.
Eye:	Flush gently with running water. Seek medical attention if irritation persists.
Skin:	Remove contaminated clothing and gently flush affected areas with water. Seek medical attention if irritation develops. Launder clothing before reuse.
Inhaled:	If over exposure occurs leave exposure area immediately. If irritation persists, seek medical attention.

PRECAUTIONS FOR USE:

Exposure Standards:	An exposure standard has not been allocated to the ingredients contained in this product.
Ventilation:	Ensure adequate natural ventilation.
Personal Protection:	Wear splash-proof goggles and PVC or rubber gloves. When using large quantities or where heavy contamination is likely, wear coveralls.
Flammability:	Non-flammable. No fire or explosion hazard exists. If the water is evaporated the residue should be considered combustible.

CONTACT POINT

Contact:	Wally Day 03 9338 6655
-----------------	---------------------------