PDS



1800 255 349 I techadvice@allfasteners.com.au

PRO88 BucketBarrow™ Wheelbarrow

The PRO88 BucketBarrow™ is the little brother to the PRO130d but don't be fooled it has all the roughness and durability required for maneuvering heavy loads.

Compact in size yet large in load carry capacity the **PRO88**'s overall width of just 525mm enables easy access and operation in narrow and difficult to access work environments.

The low centre of gravity and its broad footprint provides excellent stability for safe and efficient material loading from the 88 litre tray. The toughened poly tray is supported with a heavy duty frame.



BucketBarrow™ PRO88 trade quality narrow wheelbarrow is ideal for your building and construction, industrial, landscaping, agricultural, animal care and horticultural environments. Its narrow design and large load carry capacity excel high density property and construction environments and its compact size enables easy storage on site and in work vehicles

- PRO88's reinforced, boltless, waterproof, 5mm thick poly tray with integrated shock board provides extra durability in tough working conditions.
- The large flat tray surface enables accurate material loading and unloading, maximum load stacking capacity and easy cleaning.
- A tough slam bracket absorbs impact and protects the front of the tray when the PRO88 is tipped forward.
 PRO88's low centre of gravity enables effective movement of large volumes of materials around the work site
- Its broad footprint provides excellent stability for safe and efficient material loading and unloading.
- Comfort moulded, slip resistant hand grips enable controlled load movement and handling in tough site conditions.

PRO88 BucketBarrow™ Specifications

Load Carry Capacity	Narrow overall product width 525mm.
Tray	88 litre boltless 5mm thick UV treated premium polypropylene
Tray mounts	6 x M8 bolts mounted through 12 x 8mm heavy duty tabs
Shock Board	Integrated within the tray with strengthened ribbing
Under Tray Braces	Powder-coated tubular steel
Front Slam Bracket	4mm powder-coated steel
Handles	20 x 25mm powder-coated steel
Sub Frame	25mm heavy duty fully welded powder-coated tubular steel
Hand Grips	Comfort moulded non-slip
Tyre	380mm x 100mm heavy duty 4 ply pneumatic tough tread tyre

1800 255 349 I techadvice@allfasteners.com.au

Rim	Powder-coated fully welded steel rim with a 25mm steel axle
Bearings	Heavy duty stainless steel
Max Load Rating	180kg

1800 255 349 I techadvice@allfasteners.com.au

PRODUCT LIST

SKU	Item	Wheels	Load	Bx. Qty.	Crt. Qty.
12BBPRO88W	PRO88 BucketBarrow Wheelbarrow	1	180kg / 88L	1	-



