JOINT BACKING ROD



SKU: 11BROC

Open Cell Backing Rod is manufactured from **open cell low density polyurethane foam**. The product is manufactured in a range of sizes and has excellent compression and recovery properties.

- Compatible with all leading joint ealants
- Eliminates sealant bubbling and more breathable
- Smaller joint
- More compressable than other backing rods
- Round profile enables sealant to form correct profile for optimum movement
- Minimises the amount of sealant required
- Suitable for horizontal and vertical joints, internal walls, and glass applications
- Conforms easily to irregular shaped joints
- Does not discolour or stain
- Non-adhering to sealants
- Made in Australia




PHYSICAL CHARACTERISTICS

Material: Low density polyurethene open cell foam

Density: 27kg/m3 nominal
Service Tempurature: -40C to +70C
Tensile Strength: 85KPa
Compression Set: 90%

Resilience: 40% minimumTear Resistance: 250 N/m minimum

Flexibility: Excellent



SKU	Dia x Coil Length	No. Coil per Bale	Metre per Bale	*	
11BROC10.210	10mm x 210mtr	25	5250	1	25
11BROC16.150	16mm x 150mtr	20	3000	1	20
11BROC22.100	22mm x 100mtr	15	1500	1	15
11BROC29.60	29mm x 60mtr	15	900	1	15
11BROC38.30	38mm x 30mtr	15	450	1	15

Customer Service 1800 255 349 | techadvice@allfasteners.com.au | www.allfasteners.com.au

Allfasteners® 78-84 Logistics Street Keilor Park VIC 3042 Australia +61 3 9330 0555 Allfasteners Pty Ltd. ACN 113 948 100 ABN 86 766 075 300 Copyright © 2021. The contents of this document remains the property of Allfasteners® and may not be reproduced without prior written permission.